


ELGEF Plus Electrofusion Fittings

53 91 16



Coupler with integral pipe fixation

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Removable centre stop



PF 2 51 312 001


d [mm]	Code	GP	kg	d1 [mm]	L [mm]
20	753 911 606	50	0.054	31	68
25	753 911 607	50	0.060	36	68
32	753 911 608	50	0.072	44	72
40	753 911 609	50	0.100	54	80
50	753 911 610	10	0.136	66	88
63	753 911 611	10	0.194	81	96

53 91 16



Coupler

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Removable centre stop up to d160



PF 2 51 312 002


d [mm]	Code	d1 [mm]	L [mm]
75	753 911 612	96	110
90	753 911 613	113	125
110	753 911 614	138	145
125	753 911 615	154	158
140	753 911 616	172	168
160	753 911 617	196	180
180	753 911 618	219	194
200	753 911 619	244	208
225	753 911 620	273	224
250	753 911 621	304	244
280	753 911 622	340	252
315	753 911 623	382	268
355	753 911 624	432	290
400	753 911 625	487	290

53 91 18



Coupler

- PE 100 SDR 17 (ISO S8)
- 5 bar Gas / 10 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- d160 with removable centre stop



PF 2 51 312 002

d [mm]	Code	GP	kg	d1 [mm]	L [mm]
160	753 911 817	6	1.050	186	180
180	753 911 818	5	1.450	213	194
200	753 911 819	4	1.800	233	208
225	753 911 820	3	2.385	261	224
250	753 911 821	2	4.345	304	244
280	753 911 822	1	5.675	340	252
315	753 911 823	1	8.000	382	268
355	753 911 824	1	8.200	414	290
400	753 911 825	1	15.993	487	290
450	753 911 826	1	16.000	522	313
500	753 911 827	1	19.000	579	343